



TEST REPORT

MODEL NAME : UP6oS12WH

1. DESIGN VERIFY TEST
 - 1-1. INPUT FUNCTION TEST
 - 1-2. OUTPUT FUNCTION TEST
 - 1-3. PROTECTION FUNCTION TEST
2. SAFETY TEST
3. RELIABILITY TEST

1. DESIGN VERIFY TEST

1-1. INPUT FUNCTION TEST

TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
VOLTAGE RANGE	90~305VAC	I/P: testing O/P:full load Ta:25 °C	test ok	P
FREQUENCY RANGE	47~63Hz no damage osc	I/P:90~305VAC O/P:full~min. load Ta:25 °C	test ok	P
EFFICIENCY	84% typ.	I/P:230VAC O/P:full load Ta:25 °C	84.2%	P
AC CURRENT	0.9A/115VAC typ. 0.5A/230VACtyp. 0.45A/277VAC typ.	I/P:115VAC I/P:230VAC O/P:full load Ta:25 °C	I/P:277VAC 0.86A/115VAC 0.47A/230VAC 0.43A/277VAC	P
INRUSH CURRENT	40A typ. cold start	I/P:230VAC O/P:full load Ta:25 °C	44.8A	P
LEAKAGE CURRENT	1.5mA max.	I/P:277VAC O/P:min. load Ta:25 °C	1.1mA	P

1-2. OUTPUT FUNCTION TEST

TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
RIPPLE&NOISE	170mVp-p max.	I/P:230VAC O/P:full load Ta:25 °C	70mV	P
VOLTAGE ADJ. RANGE	12V ± 5%	I/P:115VAC I/P:230VAC O/P:min. load Ta:25 °C	11~13V/115VAC 11~13V/230VAC	P
VOLTAGE TOLERANCE	12V ± 3%	I/P:90VAC/305VAC O/P:full/min. load Ta:25 °C	± 1.66%	P
LINE REGULATION	12V ± 1%	I/P:90~305VAC O/P:full load Ta:25 °C	0.08%	P

LOAD REGULATION	12V± 2%	I/P:230VAC O/P:full-min. load Ta:25 °C	± 1.66%	P
SETUP TIME	3000ms/115VAC typ. 3000ms/230VAC typ.	I/P:115VAC I/P:230VAC O/P:full load Ta:25 °C	720ms/115VAC 680ms/230VAC	P
RISE TIME	100ms/115VAC typ. 100ms/230VAC typ.	I/P:115VAC I/P:230VAC O/P:full load Ta:25	25.2ms/115VAC 26.4ms/230VAC	P
HOLD UP TIME	10ms/115VAC typ. 60ms/230VAC typ.	I/P:115VAC I/P:230VAC O/P:full load Ta:25	13.4ms/115VAC 68.4ms/230VAC	P

1-3. PROTECTION FUNCTION TEST

TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
SHORT PROTECTION	short every output 1 hour no damage	I/P:305VAC O/P:full load Ta:25 °C	no damage, recovers automatically after fault removed	P
OVER LOAD PROTECTION	110% min.	I/P:115VAC I/P:230VAC O/P:testing Ta:25 °C	150%/115VAC 140%/230VAC recovers automatically after fault removed	P
OVER VOLTAGE PROTECTION	110~140%	I/P:115VAC I/P:230VAC O/P:min. load Ta:25 °C	120%/115VAC 120%/230VAC recovers automatically after fault removed	P
OVER TEMP. PROTECTION	temp. sensor:90±10 °C no damage	I/P:230VAC O/P:full load	O.T.P active, recovers automatically after fault removed	P

2. SAFETY TEST

TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
WITHSTAND VOLTAGE	I/P-O/P:3.75KVAC/1min<10mA I/P-F/G:2KVAC/1min<10mA O/P-F/G:1.5KVAC/1min<10mA	I/P-O/P:3.75KVAC/1min I/P-F/G:2KVAC/1min O/P-F/G:1.5KVAC/1min Ta:25℃	I/P-O/P:5.6mA I/P-F/G:5.1mA O/P-F/G:2.6mA no damage	P
ISOLATION RESISTANCE	I/O-O/P:500VDC>100MΩ I/O-F/G:500VDC>100MΩ O/P-F/G:500VDC>100MΩ	I/P-O/P:500VDC I/P-F/G:500VDC O/P-F/G:500VDC Ta:25℃	I/P-O/P:∞ I/P-F/G:∞ O/P-F/G:∞ no damage	P

3. RELIABILITY TEST

TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
LOW TEMP. TURN ON TEST	turn on after 2hour	I/P:230VAC O/P:full load Ta:-20℃	test ok	P
STORAGE TEMP. TEST	no damage	1.thermal shock temp.: -40~+80℃ 2.test time low & high temp.:30min/each 3.total cycle:5cycle 4.input/output condition:static	test ok	P
THERMAL SHOCK TEST	no damage	1.thermal shock temp.: -20~+50℃ 2.test time low & high temp.:30min/each 3.total cycle:10cycle 4.input/output condition: 230VAC full load, AC on/off test (turn on 58sec,turn off 2sec)	test ok	P
VIBRATION TEST	no damage	1.CATON&1SET 1.wave form:sine wave 2.frequency:10~500Hz 3.sweep time:12min./sweep cycle 4.acceleration:5G 5.test time:72min. in each(X,Y,Z) 6.Ta:25℃	test ok	P